

Signature™ R&R Shingle

Rebutted & Rejointed Shingle Specifications



1. Signature R&R

Shakertown® R&R shingles are composed of kiln-dried Western Red Cedar Shingles. The shingles are trimmed so side edges are parallel. The butt ends are sawn smooth at right angles to the side edges.

Dimensions:

Lengths are nominal, 18" and 24". Shingle widths are random, 3" minimum and 14" maximum. 18" R&R shingles are approximately .45" thick, and 24" R&R shingles are approximately .50" thick.

Styles:

The 18" R&R shingles and 24" R&R shingles are available with a natural sawn face, sanded face or machine grooved (combed) face.

Finishes:

Manufactured in unfinished, natural Western Red Cedar. Products may be stained or painted in the field. All shingle styles are also available with a factory-applied grey or white oil primer on all sides. Factory priming will minimize the opportunity of natural extractive bleeding.

(Refer to Technical Bulletin 4001, Stains & Finishes.)

Basic Uses:

Shakertown R&R shingles are used on exterior and interior walls when a high quality shingle appearance is required. Perfect for architectural styles such as colonial, shingle-style, Victorian, rustic cabin, ranch, bungalow, contemporary and modern homes.

Packaging:

Shakertown R&R 18" shingles are packaged in one square cardboard cartons and half square cartons. 24" shingles are packed in 4-carton squares.

Coverage:

One full carton of 18" shingles covers 100 sq. ft. at 14" exposure (double course application), or 50 sq. ft. at 7" exposure (single course application). The 24" shingles are sold in 4-carton squares, with one carton covering 25 sq. ft. at 7-1/2" exposure (single course application). Refer to the coverage table for accurate material requirements.

Fasteners:

Rust-resistant, hot dipped galvanized, 4D box nails are recommended. Pneumatic siding nails with a rust resistant finish may also be used.

Weather Barrier

Apply a suitable weather-resistant barrier, such as type 15 felt or better, in accordance with local code requirements. Use a two-inch head lap and six-inch end lap when fastening barrier.

2. Technical Data.

Applicable Standards:

Number 1 Grade Shakertown R&R shingles are manufactured from Number One Grade Western Red Cedar Shingles. Finished shingles conform to commercial standard CS199-55 for natural grooved and R&R shingles.

3. Availability and Cost

Shakertown products are available throughout the United States and Canada exclusively through authorized distributors. To connect with your local sales representative for stocking locations, project guidance, or pricing information, please visit Shakertown.com and select Find a Sales Rep.

4. Maintenance.

The performance of this material will vary according to geographical conditions and quality of applied finish. For maximum performance Shakertown recommends a quality oil-based stain or finish. Please refer to Technical Bulletin 4001, Stains and Finishes.



If you have any questions regarding this product or other Shakertown materials, please contact us toll-free at **1-800-426-8970**

SHAKERTOWN® CORP.

P.O. Box 400 · 1200 Kerron Street · Winlock, WA 98596

www.shakertown.com



SHAKERTOWN.COM

COVERAGE & EXPOSURE TABLE

Each square Box provides coverage up to 100 sq. ft. for machine-grooved, Natural Sawn, or sanded-face shingles at their specified exposure (e.g., 18" @ 14" exposure = 100 sq. ft.).

Shingle length	6"	7"	8"	9"	10"	11"	12"	13"	14"	15"	16"	
18 inch*	43	50	57†	64	72	79	86	93	100‡	--	--	
24 inch**	80	93	106	120	133†	146	160	173	186	200	213‡	
*Sold in full, Half, and Quarter Boxes. **24-inch shingles are packaged in 4-carton square sets for convenient handling.						† Maximum exposure for single-course application. ‡ Maximum exposure for double-course application.						
Maximum Exposures:	18" Shingles: <ul style="list-style-type: none"> • Single-course application – 8" exposure • Double-course application – 14" exposure 					24" Shingles: <ul style="list-style-type: none"> • Single-course application – 10" exposure • Double-course application – 16" exposure 					Note: Double-course installations require undercoursing shingles for proper application.	

NOT SURE HOW MANY CARTONS YOU NEED?
Use Shakertown's conversion calculator

